SELF SERVICE REFRIGERATED DISPLAY

LUX













- k Exterior made of stainless steel 304
- k Interior stainless steel 304
- k Insulation with ecological polyurethane 5cm
- k Black colored metal shelves
- k Magnetic closing doors
- k Display LED lighting
- $\ensuremath{^{\textbf{k}}}$ Functional also with open front

- $\ensuremath{^{k}}\xspace$ Uniform cooling distribution on each shelf through air flow system
- Front removable plexiglas doors for maximize energy saving
- k Double glasses for low energy consumption
- k Fan assisted cooling
- k Height adjustable inox feet
- k Ecological freon



SELF SERVICE REFRIGERATED DISPLAY

LUX













MODEL	SBF 50
External dimensions (WxDxH) cm.	50 x 70 x 120
Temperature Range (°C)	+3 to +10
Hinged Doors	1
Inox Feet (Pcs/Dimensions (H) cm.)	4/5-7
Voltage / Frequency (V/Hz)	220 - 240 / 50
Input Power (W)	400
Compressor (HP)	3/8
Type of Cooling	Fan assisted
Type of Defrost	Automatic
Controller	Digital
Refrigerant	R 290
Internal Light	LED
Net Weight (kg)	95
Volume (m3)	0,42
PRICE	