

# US 50

## REFRIGERATED CABINET

SLIM LINE



- ⌘ Stainless steel 304 Exterior / Interior
- ⌘ Insulation with ecological polyurethane 7cm the body and 8cm on the bottom
- ⌘ H.A.C.C.P. rounded corners
- ⌘ Plastic – coated grills
- ⌘ Stainless steel pair sheet for Gastronorm Containers
- ⌘ Self - closing door

- ⌘ Terminal switch which blocks the ventilator when the door opens
- ⌘ Ecological Freon
- ⌘ Air flow system for uniform distribution of cooling
- ⌘ Wi-Fi connectivity to mobile app for temperature recording and alarms (optional)

# UK 50

## FREEZER CABINET

SLIM LINE WITH OPTIONAL DRAWERS



### Optional drawers

Drawer guides are made of stainless steel AISI 304 and have durability of 60kg

### DRAWER

MODEL	SC1
Dimensions (WxDxH) cm.	31 x 54,3 x 26
PRICE	

- κ Stainless steel Exterior/Interior
- κ Insulation with ecological polyurethane 7cm the body and 8cm on the bottom
- κ H.A.C.C.P. rounded corners
- κ Plastic-coated grills
- κ Optional gastro drawer installation
- κ Stainless steel pair sheet for gastronom containers
- κ Height adjustable inox feet
- κ Shelf-closing door, terminal switch which blocks the ventilator when the door opens
- κ Air flow system for uniform distribution of cooling
- κ Ecological freon
- κ Wi-Fi connectivity to mobile app for temperature recording and alarms (optional)

MODEL	US 50	UK 50
External dimensions (WxDxH) cm.	50 x 72 x 207	50 x 72 x 207
Capacity (L)	314	314
Temperature Range (°C)	0 to +10	0 to -20
Doors	1	1
Door Dimensions (WxD) cm.	49 x 167	49 x 167
Plastic-coated grills (Pcs/Dimensions (WxD) cm.)	3 / 33 x 53,5	3 / 33 x 53,5
Inox Feet (Pcs/Dimensions (H) cm.)	4 / 10 -13	4 / 10 -13
Voltage / Frequency (V/Hz)	220 - 240 / 50	220 - 240 / 50
Input Power (W)	450	650
Compressor (HP)	3/8	1/2
Type of Cooling	Βεβιασμένη	Βεβιασμένη
Type of Defrost	Αυτόματη	Αυτόματη
Controller	Ψηφιακός	Ψηφιακός
Refrigerant	R 290	R 290
Internal Light	LED	X
Net Weight (kg)	105	116
Volume (m3)	0,74	0,74
PRICE		