## **REFRIGERATED CABINET**

FOR TRAYS 40x60 cm.















- k Stainless steel Exterior/Interior
- k Insulation with ecological polyurethane 7 cm to the body and 8 cm on the bottom
- k H.A.C.C.P. rounded corners
- k Stainless steel construction for 17 trays 40×60 cm
- k Height adjustable inox feet

- $\ensuremath{^{\mathsf{k}}} \mathsf{Self}\text{-}\mathsf{closing}$  door, terminal switch which blocks the ventilator when the door opens
- k Ecological freon
- k Air flow system for uniform distribution of cooling
- kWi-Fi connectivity to mobile app for temperature recording and alarms (optional)



## **FREEZER CABINETS**

FOR TRAYS 40x60 cm.













- k Stainless steel Exterior/Interior
- Insulation with ecological polyurethane 7 cm to the body and 8 cm on the bottom
- k H.A.C.C.P. rounded corners
- k Stainless steel construction for 17 trays 40×60 cm
- k Height adjustable inox feet

- kSelf-closing door, terminal switch which blocks the ventilator when the door opens
- k Ecological freon
- k Air flow system for uniform distribution of cooling
- Wi-Fi connectivity to mobile app for temperature recording and alarms (optional)

MODEL	UST 70	UKT 70
External dimensions (WxDxH) cm.	70 x 82 x 207	70 x 82 x 207
Capacity (L)	620	620
Temperature Range (°C)	-1 to +10	0 to -20
Doors	1	1
Door Dimensions (WxD) cm.	69 x 164,6	69 x 164,6
Tray dimensions (Pcs/Dimensions (WxD) cm.)	17 / 40 x 60	17 / 40 x 60
Inox Feet (Pcs/Dimensions (H) cm.)	4/10-13	4/10-13
Voltage / Frequency (V/Hz)	220 - 240 / 50	220 - 240 / 50
Input Power (W)	450	650
Compressor (HP)	3/8	1/2
Type of Cooling	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic
Controller	Digital	Digital
Refrigerant	R 290	R 290
Internal Light	LED	<del>-</del>
Net Weight (kg)	115	127
Volume (m³)	1,18	1,18
PRICE		